

## SAFETY DATA SHEET

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

Ref.	130000007547/
Rev. no.	1.0
Revision Date	10.01.2024
Print Date	23.01.2024

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Trade name SÜDWEST AquaVision Holz-Imprägnier-Grund WV

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Wood preservatives  
Biocidal product

Uses advised against This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
Iggelheimer Str. 13  
D - 67459 Böhl-Iggelheim  
Telephone: +49 6324/709-0  
Telefax: +49 6324/709-175  
[www.suedwest.de](http://www.suedwest.de)

E-mail address of person  
responsible for the SDS  
European Union [sdb@suedwest.de](mailto:sdb@suedwest.de)

**1.4 Emergency telephone  
number** European Union Phone: +44 (0) 1865 407333

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P102 Keep out of reach of children.

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

**Prevention:**

P273 Avoid release to the environment.

**Disposal:**

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

**Additional Labelling**

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1), 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

**Regulation concerning biocidal products (528/2012):**

To avoid risks to man and the environment, comply with the instructions for use.

Not to be used in conjunction with wood which is intended for direct contact with foods or animal feed.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
3-iodo-2-propynyl butylcarbamate	55406-53-6 259-627-5 616-212-00-7 01-2120762115-60-XXXX	STOT RE 1; H372 (larynx) Eye Dam. 1; H318 Acute Tox. 3; H331 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute Tox. 4; H302  M-Factor (Acute aquatic	≥ 0,25 - < 1

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

		toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60-XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1  specific concentration limit Skin Sens. 1 ≥ 0,05 %	≥ 0,005 - < 0,05
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)	55965-84-9  613-167-00-5 01-2120764691-48-XXXX	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 EUH071  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1C ≥ 0,6 % Skin Irrit. 2 0,06 - < 0,6 % Eye Irrit. 2 0,06 - < 0,6 % Skin Sens. 1A ≥ 0,0015 % Eye Dam. 1 ≥ 0,6 %	≥ 0,0002 - < 0,0015

For explanation of abbreviations see section 16.

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice	First aider needs to protect himself. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
----------	---------------------------

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat symptomatically. No information available.
-----------	-----------------------------------------------------

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical Water spray
Unsuitable extinguishing media	High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Wear self-contained breathing apparatus for firefighting if necessary.

### 5.3 Advice for firefighters

Additional advice	Use personal protective equipment. Complete suit protecting against chemicals Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be
-------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

disposed of in accordance with local regulations.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.  
Do not breathe vapour.

### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Dispose of contaminated material as waste according to item 13.  
Clean contaminated surface thoroughly.

### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

#### Advice on safe handling

Avoid contact with skin and eyes.  
Prevent unauthorized access.

#### Hygiene measures

Provide sufficient air exchange and/or exhaust in work rooms.  
Comply with the statutory regulations on health and safety at work.  
Wash hands before breaks and at the end of workday.  
When using do not eat, drink or smoke.  
Remove and wash contaminated clothing and gloves, including the inside, before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage areas and containers

Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in original container.  
Observe label precautions.  
Protect from frost, heat and sunlight.

#### Advice on common storage

Keep away from oxidizing agents and strongly acid or alkaline materials.

#### Storage temperature

5 - 30 °C

### 7.3 Specific end use(s)

For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation.

### Individual protection measures, such as personal protective equipment (PPE)

- |                           |                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| a) Eye/face protection    | Wear protective goggles for protection against splashed liquid.                                                                                                                                                                                                                                                                                                                                   |
| b) Skin protection        | Safety glasses with side-shields conforming to EN166                                                                                                                                                                                                                                                                                                                                              |
| Hand protection           | Break through time: 480 min<br>Minimum thickness: 0,4 mm<br>Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.<br>Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.        |
| Body Protection           | The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.<br>The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.<br>Work clothes<br>Skin should be washed after contact.<br>Do NOT use solvents or thinners. |
| c) Respiratory protection | No personal respiratory protective equipment normally required.<br>In case of insufficient ventilation, wear suitable respiratory equipment.<br>Employees involved in spraying work or in the immediate vicinity of such work should use a P2 particle filter against spray fog.<br>Respiratory protection complying with EN 143.                                                                 |

### Environmental exposure controls

- |                |                                                                                                                                                                        |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General advice | The product should not be allowed to enter drains, water courses or the soil.<br>If the product contaminates rivers and lakes or drains inform respective authorities. |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	liquid
Colour	various
Odour	mild

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

Odour Threshold	No data available
pH	ca. 8 (20 °C)
Melting point/freezing point	No data available
Initial boiling point and boiling range	No data available
Flash point	Not applicable
Evaporation rate	not applicable
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	No data available
Lower explosion limit / Lower flammability limit	No data available
Vapour pressure	No data available
Vapour density	No data available
Density	ca. 1,0 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	
Water solubility	soluble
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity	
Viscosity, dynamic	No data available

## 9.2 Other information

Flow time	ca. 10 s at 20 °C Cross section: 4 mm
-----------	------------------------------------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

Hazardous reactions

This information is not available.

## 10.4 Conditions to avoid

Conditions to avoid

Stable under recommended storage and handling conditions  
(see section 7).

## 10.5 Incompatible materials

Materials to avoid

Strong acids and strong bases  
Strong oxidizing agents

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity

Based on available data, the classification criteria are not met.

Acute inhalation toxicity

Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity

Based on available data, the classification criteria are not met.

#### Components:

##### **3-iodo-2-propynyl butylcarbamate:**

Acute oral toxicity

Harmful if swallowed.

Acute inhalation toxicity

LC50 (Rat): 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

##### **1,2-benzisothiazol-3(2H)-one:**

Acute oral toxicity

LD50 (Rat): 532 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity

LC50 (Rat): 0,4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Acute oral toxicity

Toxic if swallowed.

Acute inhalation toxicity

Assessment: Corrosive to the respiratory tract.  
Fatal if inhaled.



# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

Acute dermal toxicity

Fatal in contact with skin.

## Skin corrosion/irritation

### Product:

Based on available data, the classification criteria are not met.

### Components:

#### 1,2-benzisothiazol-3(2H)-one:

Causes skin irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes severe skin burns and eye damage.

## Serious eye damage/eye irritation

### Product:

Based on available data, the classification criteria are not met.

### Components:

#### 3-iodo-2-propynyl butylcarbamate:

Causes serious eye damage.

#### 1,2-benzisothiazol-3(2H)-one:

Causes serious eye damage.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes serious eye damage.

## Respiratory or skin sensitisation

### Product:

Based on available data, the classification criteria are not met.

### Components:

#### 3-iodo-2-propynyl butylcarbamate:

May cause an allergic skin reaction.

#### 1,2-benzisothiazol-3(2H)-one:

May cause an allergic skin reaction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

May cause an allergic skin reaction.

## Germ cell mutagenicity

### Product:

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

## Carcinogenicity

### Product:

Based on available data, the classification criteria are not met.

## Reproductive toxicity

### Product:

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**STOT - single exposure**

**Product:**

Based on available data, the classification criteria are not met.

**STOT - repeated exposure**

**Product:**

Based on available data, the classification criteria are not met.

**Components:**

**3-iodo-2-propynyl butylcarbamate:**

Exposure routes

Inhalation

Target Organs

larynx

Assessment

Causes damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

**Product:**

Based on available data, the classification criteria are not met.

**Further information**

**Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## 11.2 Information on other hazards

**Endocrine disrupting properties**

**Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Further information**

**Product:**

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

**Product:**

Toxicity to fish

No data available

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

## Components:

### **3-iodo-2-propynyl butylcarbamate:**

Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 0,067 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 0,16 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	EC50 (Pseudokirchneriella subcapitata (green algae)): 0,049 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  NOEC (Pseudokirchneriella subcapitata (green algae)): 0,0046 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	10
Toxicity to fish (Chronic toxicity)	NOEC: 0,0084 mg/l Exposure time: 35 d Species: Pimephales promelas (fathead minnow)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 0,010 mg/l Exposure time: 21 d Species: Daphnia (water flea) Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	1
<b>1,2-benzisothiazol-3(2H)-one:</b>	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 2,2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia (water flea)): 3,27 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  NOEC (Selenastrum capricornutum (green algae)): 0,04 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	1
Toxicity to fish (Chronic)	NOEC: 0,21 mg/l

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

toxicity)	Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 215
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 1,2 mg/l Exposure time: 21 d Species: Daphnia (water flea) Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	1
<b>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):</b>	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia (water flea)): 0,12 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l Exposure time: 48 h  NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l Exposure time: 48 h
M-Factor (Acute aquatic toxicity)	100
Toxicity to fish (Chronic toxicity)	NOEC: 0,098 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 0,004 mg/l Exposure time: 21 d Species: Daphnia (water flea)
M-Factor (Chronic aquatic toxicity)	100
<b>12.2 Persistence and degradability</b>	
<b><u>Product:</u></b>	
Biodegradability	No data available
<b><u>Components:</u></b>	
<b>3-iodo-2-propynyl butylcarbamate:</b>	
Biodegradability	rapidly degradable
<b>1,2-benzisothiazol-3(2H)-one:</b>	
Biodegradability	not rapidly degradable
<b>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):</b>	
Biodegradability	not rapidly degradable

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation No data available

### Components:

#### **3-iodo-2-propynyl butylcarbamate:**

Partition coefficient: n-octanol/water log Pow: 2,8

#### **1,2-benzisothiazol-3(2H)-one:**

Partition coefficient: n-octanol/water log Pow: 0,7  
Method: OECD Test Guideline 117

## 12.4 Mobility in soil

### Product:

Mobility No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. Dispose of as special waste in compliance with local and national regulations. Partial and residual quantities can be reused. Do not pour into the drain. - Do not allow to enter into the sewerage system.
Contaminated packaging	Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.
Waste key for the unused	03 02 05* other wood preservatives containing hazardous

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

product

substances

(\*) hazardous waste in terms of the European directive  
2008/98/EG**SECTION 14: TRANSPORT INFORMATION****14.1 UN number or ID number**

Not regulated as a dangerous good

**14.2 UN proper shipping name**

Not regulated as a dangerous good

**14.3 Transport hazard class(es)**

Not regulated as a dangerous good

**14.4 Packing group**

Not regulated as a dangerous good

**14.5 Environmental hazards****14.6 Special precautions for user**

Remarks

This information is not available.

**14.7 Maritime transport in bulk according to IMO instruments**

Remarks

Not applicable

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC

Directive 2010/75/EU

0 %

VOC

Directive 2004/42/EC

0 %

EU limit value for this product (cat. A/h) :30 g/lThis product  
contains max30 g/lVOC.Regulation (EU) No 649/2012  
of the European Parliament

Not applicable

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

and the Council concerning the  
export and import of dangerous  
chemicals

**Notification status**

The product falls under the regulation on biocide products (EU)  
528/2012.

**Further notes**

Do not use in the direct vicinity of bodies of water. Do not allow the  
agent or any product residues to enter into waters, the soil or the  
sewage system.  
The effectiveness of the biocide is dependent on correct storage  
and observation of the use-by date.

**Other regulations**

Comply with the statutory regulations on health and safety at work.

**15.2 Chemical safety assessment**

This information is not available.

**SECTION 16: OTHER INFORMATION**

**Changes from the previous version are indicated by markings in the left-hand margin.  
The information in this Safety Data Sheet corresponds to our present state of  
knowledge and conforms to both national and EU legislation. The user's working  
conditions are, however, beyond our knowledge and control. The user is responsible  
for complying with all necessary legal requirements. The information in this Safety Data  
Sheet describes the safety requirements of our product and does not constitute any  
assurance of product properties.**

**Full text of H-Statements**

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H331	: Toxic if inhaled.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

# SÜDWEST AquaVision Holz- Imprägnier-Grund WV

STOT RE : Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

### Other information

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de



# **SÜDWEST AquaVision Holz- Imprägnier-Grund WV**