

## SAFETY DATA SHEET

# SÜDWEST PALADUR hochglänzend

Ref.	130000006137/
Rev. no.	1.2
Revision Date	27.06.2018
Print Date	17.07.2018

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Trade name SÜDWEST PALADUR hochglänzend

Product code 30920-001

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Coating compound/ Surface coating/ paint

Uses advised against This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
Iggelheimer Str. 13  
D - 67459 Böhl-Iggelheim  
Telephone: +49 6324/709-0  
Telefax: +49 6324/709-175  
[www.suedwest.de](http://www.suedwest.de)

E-mail address of person responsible for the SDS  
European Union [sdb@suedwest.de](mailto:sdb@suedwest.de)

#### 1.4 Emergency telephone number European Union

Phone: +44 (0)1235 239 670

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids,  
Category 3

H226: Flammable liquid and vapour.

# SÜDWEST PALADUR

## hochglänzend

### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	Warning	
Hazard statements	H226	Flammable liquid and vapour.
Supplemental Hazard Statements	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	P102	Keep out of reach of children.
	<b>Prevention:</b> P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	<b>Response:</b> P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	<b>Disposal:</b> P501	Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Has a narcotising effect.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

Chemical nature Alkyd resin based paint.

#### Hazardous components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC))	Concentration (% w/w)

# SÜDWEST PALADUR

## hochglänzend

	Registration number	No 1272/2008)	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9  01-2119457273-39-XXXX	Asp. Tox.1; H304  The CAS number is no longer specified in REACH registration, but still serves as identification in other areas.	≥ 25 - < 50
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9  01-2119471843-32-XXXX	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic3; H412  Note P The CAS number is no longer specified in REACH registration, but still serves as identification in other areas.	≥ 3 - < 5
2-Ethylhexanoic acid, zirconium salt	22464-99-9 245-018-1 01-2119979088-21-XXXX	Repr.2; H361d	≥ 0,1 - < 0,3

For explanation of abbreviations see section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

##### General advice

When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.  
If unconscious, place in recovery position and seek medical advice.

##### Inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If symptoms persist, call a physician.

##### Skin contact

Take off contaminated clothing and shoes immediately.

# SÜDWEST PALADUR

## hochglänzend

Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
If skin irritation persists, call a physician.

Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. If swallowed, seek medical advice immediately and show this container or label. Keep at rest. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	Inhalation may provoke the following symptoms: Headache Dizziness Drowsiness Unconsciousness
----------	--

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat symptomatically. No information available.
-----------	---

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable extinguishing media	CO <sub>2</sub> , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
------------------------------	---

Unsuitable extinguishing media	High volume water jet
--------------------------------	-----------------------

#### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.

# SÜDWEST PALADUR

## hochglänzend

Additional advice

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

#### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.  
Dispose of contaminated material as waste according to item 13.

#### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Advice on safe handling

Comply with the statutory regulations on health and safety at work.  
Avoid formation of aerosol.  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
All metal parts of the mixing and processing equipment must be earthed.  
Operators should wear antistatic footwear and clothing. No sparking tools should be used.

Hygiene measures

Do not breathe spray, vapour.

# SÜDWEST PALADUR

## hochglänzend

Take off immediately all contaminated clothing.  
Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
After washing hands, replenish lost skin oil by means of oily skin ointment.  
When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Store in original container. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nonsmoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a well-ventilated place. Protect from frost, heat and sunlight.
Advice on protection against fire and explosion	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
Advice on common storage	Keep away from combustible materials. Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or alkaline materials.

**7.3 Specific end use(s)** For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

The lists that were valid during the creation were used as basis. Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Appropriate engineering controls

# SÜDWEST PALADUR

## hochglänzend

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn. Washing facilities / water for rinsing eyes and skin should be available.

### Individual protection measures, such as personal protective equipment

- a) Eye/face protection                      Safety glasses with side-shields conforming to EN166
- b) Skin protection  
Hand protection                              Break through time: 480 min  
Minimum thickness: 0,4 mm  
Gloves made of nitrile rubber, e.g. KCL 730 Camatril®  
Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-  
87-300, kcl-uk@kcl.de), or equivalent.  
Skin that comes into contact with the product should be  
treated with protective cream. After such contact, the  
product concerned should under no circumstances be used.
- The selected protective gloves have to satisfy the  
specifications of EU Directive 89/686/EEC and the standard  
EN 374 derived from it.  
The choice of an appropriate glove does not only depend on  
its material but also on other quality features and is different  
from one producer to the other.
- Body Protection                              Preventive skin protection  
Long sleeved clothing  
Personal should wear antistatic clothings made of natural  
fiber or of high temperature resistant synthehc fiber. All  
parts of the body should be washed after contact.
- c) Respiratory protection                    When workers are facing concentrations above the  
occupational exposure limit values they must use  
appropriate certified respirators.  
Breathing protection equipment required in inadequately  
ventilated places and during spraying.  
In order to avoid inhalation of spray-mist and sanding dust,  
all spraying and sanding must be done wearing adequate  
respirator.  
Combination filter A-P2  
Respiratory protection complying with EN 14387.

### Environmental exposure controls

- General advice                              The product should not be allowed to enter drains, water  
courses or the soil.  
If the product contaminates rivers and lakes or drains  
inform respective authorities.

# SÜDWEST PALADUR

## hochglänzend

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Appearance	liquid
Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	not determined
Melting point/freezing point	No data available
Initial boiling point and boiling range	200 °C
Flash point	50 °C
Evaporation rate	not applicable
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	7,0 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	0,6 %(V) Lower explosion limit
Vapour pressure	1 hPa (20 °C)
Density	ca. 0,915 g/cm <sup>3</sup>
Solubility(ies) Water solubility	insoluble
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	236 °C
Decomposition temperature	No data available
Viscosity	



# SÜDWEST PALADUR

## hochglänzend

Viscosity, kinematic	No data available
Explosive properties	Not explosive
Oxidizing properties	Not applicable

### 9.2 Other information

Self-ignition	not auto-flammable
Flow time	92 s Cross section: 4 mm

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	No dangerous reaction known under conditions of normal use. Vapours may form explosive mixture with air.
---------------------	---

### 10.4 Conditions to avoid

Conditions to avoid	Direct sources of heat. Strong sunlight for prolonged periods.
---------------------	---

### 10.5 Incompatible materials

Materials to avoid	Strong acids and strong bases Strong oxidizing agents
--------------------	--

### 10.6 Hazardous decomposition products

Hazardous decomposition products	No decomposition if stored and applied as directed.
Decomposition temperature	No data available

## SECTION 11: TOXICOLOGICAL INFORMATION

# SÜDWEST PALADUR

## hochglänzend

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity                      Based on available data, the classification criteria are not met.

Acute inhalation toxicity              Based on available data, the classification criteria are not met.

Acute dermal toxicity                    Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

##### Product:

Repeated exposure may cause skin dryness or cracking.

##### Components:

#### || Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Repeated exposure may cause skin dryness or cracking.

#### || Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Repeated exposure may cause skin dryness or cracking.

#### Serious eye damage/eye irritation

##### Product:

Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

##### Product:

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

##### Product:

Genotoxicity in vitro                    Based on available data, the classification criteria are not met.

#### Carcinogenicity

##### Product:

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

##### Product:

Effects on fertility                        Based on available data, the classification criteria are not met.

# SÜDWEST PALADUR

## hochglänzend

Developmental Toxicity                      Based on available data, the classification criteria are not met.

**Components:**

**|| 2-Ethylhexanoic acid, zirconium salt:**

Developmental Toxicity                      Suspected of damaging the unborn child.

**STOT - single exposure**

**Product:**

Based on available data, the classification criteria are not met.

**Components:**

**|| Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Assessment                                      May cause drowsiness or dizziness.

**STOT - repeated exposure**

**Product:**

Based on available data, the classification criteria are not met.

**Aspiration toxicity**

**Product:**

Based on available data, the classification criteria are not met.

**Components:**

**|| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

May be fatal if swallowed and enters airways.

**|| Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

May be fatal if swallowed and enters airways.

**Experience with human exposure**

**Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.  
Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible

# SÜDWEST PALADUR

## hochglänzend

damage to the eye.

### Further information

#### Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish                      No data available

### 12.2 Persistence and degradability

#### Product:

Biodegradability                      No data available

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation                      No data available

#### Components:

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics :**

Partition coefficient: n-              log Pow: 4  
octanol/water

### 12.4 Mobility in soil

#### Product:

Mobility                                  No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment                              This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

#### Product:

# SÜDWEST PALADUR

## hochglänzend

Additional ecological  
information

Do not allow product to enter into ground water, bodies  
of water or sewage systems.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Product	<p>The user is responsible for proper coding and marking of any waste.</p> <p>When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"</p> <p>Partial and residual quantities can be reused.</p> <p>Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.</p>
Contaminated packaging	<p>Packaging that is not properly emptied must be disposed of as the unused product.</p> <p>Empty packaging should be recycled through disposal systems.</p>
Waste key for the unused product	<p>08 01 11* Paint and varnish waste containing organic solvents or other dangerous substances</p> <p>(* ) hazardous waste in terms of the European directive 91/689/EEC</p>

### SECTION 14: TRANSPORT INFORMATION

#### 14.1 UN number

ADR 1263

IMDG 1263

IATA 1263

#### 14.2 UN proper shipping name

ADR PAINT

IMDG PAINT

# SÜDWEST PALADUR

## hochglänzend

IATA Paint

### 14.3 Transport hazard class(es)

ADR 3

IMDG 3

IATA 3

### 14.4 Packing group

#### ADR

Packing group III

Classification Code F1

Hazard Identification  
Number 30

Labels 3

Tunnel restriction code (D/E)

#### IMDG

Packaging group III

Labels 3

EmS number F-E, S-E

#### IATA

Packaging group III

Labels 3

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous no

#### IMDG

Marine pollutant no

### 14.6 Special precautions for user

# SÜDWEST PALADUR

## hochglänzend

Remarks This information is not available.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks Not applicable

### Additional advice

ADR ADR: Packages < 450l: No dangerous goods (ADR 2.2.3.1.5)  
IMDG IMDG: Packages < 30l: No dangerous goods (IMDG 2.3.2.5).

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU 47,1 %  
430,5 g/l

VOC  
Directive 2004/42/EC 47,23 %  
432,13 g/l

EU limit value for this product (cat. A/i) :500 g/lThis product contains max500 g/IVOC.

Regulation (EC) No  
649/2012 of the European  
Parliament and the Council  
concerning the export and  
import of dangerous  
chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.

# SÜDWEST PALADUR

## hochglänzend

### 15.2 Chemical safety assessment

This information is not available.

### SECTION 16: OTHER INFORMATION

**Changes from the previous version are indicated by markings in the left-hand margin.**

**The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

#### Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H336	: May cause drowsiness or dizziness.
H361d	: Suspected of damaging the unborn child.
H412	: Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test



# SÜDWEST PALADUR

## hochglänzend

population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing  
MSDS  
REG\_EU / EN

sdb@suedwest.de

**SÜDWEST PALADUR**  
**hochglänzend**