

# SÜDWEST SolSilikat Fassadenfarbe

Ref.	130000006893/
Rev. no.	1 1
Revision Date	12.11.2018
Print Date	17.01.2019

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

<b>1.1 Product identifier</b> Trade name	SÜDWEST SolSilikat Fassadenfarbe
1.2 Relevant identified uses of the substance or mixture and uses advised against	Facade paint
Uses advised against	This information is not available.
1.3 Details of the supplier of the safety data sheet	SÜDWEST Lacke + Farben GmbH & Co.KG Iggelheimer Str. 13 D - 67459 Böhl-Iggelheim Telephone: +49 6324/709-0 Telefax: +49 6324/709-175 www.suedwest.de
E-mail address of person responsible for the SDS European Union	sdb@suedwest.de
<b>1.4 Emergency</b> telephone number European Union	Phone: +44 (0)1235 239 670

### SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

# SÜDWEST SolSilikat Fassadenfarbe

Additional Labelling:

May contain traces of preservatives, due to raw materials.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The product is alkaline.

Avoid contact with the skin and the eyes.

The potassium silicate contained in this product (aqueous solution, molar ratio > 3.2 and solid content < 40%) is not subject to marking requirements. Its classification is based on toxicological tests carried out by the CEES (European Centre for Silicate Research - www.cees-silicates.org)

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<b>3.2 Mixtures</b> Chemical nature	Water dilutable, dispersion-silicate based paint
Hazardous components Remarks	: No hazardous ingredients
	SECTION 4: FIRST AID MEASURES
4.1 Description of first a	id measures
General advice	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash off immediately with soap and plenty of water. Do NOT use solvents or thinners. If symptoms persist, call a physician. Wash contaminated clothing before re-use.

# SÜDWEST SolSilikat Fassadenfarbe

Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.
4.2 Most important symptoms and effects, both acute and delayed	

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms
----------

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat
	No in

Treat symptomatically. No information available.

### **SECTION 5: FIREFIGHTING MEASURES**

### 5.1 Extinguishing media

Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray
Unsuitable extinguishing media	High volume water jet
5.2 Special hazards arising from the substance or mixture	Fire may cause evolution of: Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx) Exposure to decomposition products may be a hazard to health.
5.3 Advice for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.
Additional advice	Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal	Ensure adequate ventilation.
precautions, protective equipment and	

# SÜDWEST SolSilikat Fassadenfarbe

emergency procedures 6.2 Environmental precautions	The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Sweep up and shovel. Clean with detergents. Avoid solvents. Dispose of contaminated material as waste according to item 13. Clean contaminated surface thoroughly.
6.4 Reference to other sections	Refer to protective measures listed in sections 7 and 8.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Advice on safe handling	Do not get in eyes or mouth or on skin. Prevent unauthorized access. Provide sufficient air exchange and/or exhaust in work rooms. Comply with the statutory regulations on health and safety at work.
Hygiene measures	Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke. Avoid contact with the skin and the eyes. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Keep in a dry place. Observe label precautions. Protect from frost, heat and sunlight.
Advice on protection	When exposed to high temperatures may produce

# SÜDWEST SolSilikat Fassadenfarbe

against fire and explosion	hazardous decomposition products such as carbon monoxide and dioxide, fumes.
Advice on common storage	Keep away from oxidizing agents and strongly acid or alkaline materials.
7.3 Specific end use(s)	For further information, see also Technical Data Sheet for the product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

### 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation.

#### Individual protection measures, such as personal protective equipment

a) Eye/face protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
b) Skin protection	
Hand protection	Break through time: 480 min Minimum thickness: 0,4 mm Gloves made of nitrile rubber,e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659- 87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.
	The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
Body Protection	Impervious clothing Skin should be washed after contact.
c) Respiratory protection	Employees involved in spraying work or in the immediate

# SÜDWEST SolSilikat Fassadenfarbe

vicinity of such work should use a P2 particle filter against spray fog. Respiratory protection complying with EN 143.

### Environmental exposure controls

General advice The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	liquid
Colour	various
Odour	Weak, characteristic
Odour Threshold	No data available
рН	ca. 11,2
Melting point/freezing point	> 0 °C
Initial boiling point and boiling range	No data available
Flash point	> 100 °C
Evaporation rate	not applicable
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	No data available
Lower explosion limit / Lower flammability limit	No data available
Vapour pressure	No data available
Vapour density	No data available
Density	ca. 1,51 g/cm3 (20 °C)
Solubility(ies)	

## according to Regulation (EC) No. 1907/2006

## SAFETY DATA SHEET

# SÜDWEST SolSilikat Fassadenfarbe

Water solubility	completely miscible
Partition coefficient: n- octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity Viscosity, dynamic	ca. 1.600 - 2.600 mPa.s
Explosive properties	Not explosive
Oxidizing properties	Not applicable
9.2 Other information	

### SECTION 10: STABILITY AND REACTIVITY

No data available

### 10.1 Reactivity

Flow time

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions This information is not available.

### 10.4 Conditions to avoid

Conditions to avoid	Stable under recommended storage and handling
	conditions (see section 7).

### 10.5 Incompatible materials

Materials to avoid	Strong acids
	Oxidizing agents

### **10.6 Hazardous decomposition products**

Hazardous decomposition	No decomposition if stored and applied as directed.
products	
Decomposition	No data available
temperature	

# SÜDWEST SolSilikat Fassadenfarbe

### SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects Acute toxicity	
Product: Acute oral toxicity	Based on available data, the classification criteria are not met.
Acute inhalation toxicity	Based on available data, the classification criteria are not met.
Acute dermal toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	
Product:	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	
<u>Product:</u>	Based on available data, the classification criteria are not met.
Respiratory or skin sensitis	ation
<u>Product:</u>	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	
<u>Product:</u> Genotoxicity in vitro	Based on available data, the classification criteria are not met.
Carcinogenicity	
<u>Product:</u>	Based on available data, the classification criteria are not met.
Reproductive toxicity	
<u>Product:</u> Effects on fertility	Based on available data, the classification criteria are not met.
Developmental Toxicity	Based on available data, the classification criteria are not met.

# SÜDWEST SolSilikat Fassadenfarbe

STOT - single exposure <u>Product:</u>

Based on available data, the classification criteria are not met.

### STOT - repeated exposure Product:

Based on available data, the classification criteria are not met.

Aspiration toxicity <u>Product:</u> Based on available data, the classification criteria are not met.

## Experience with human exposure Product:

General Information Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Danger of irritation to eyes, nose, throat and the air passages.

### Further information <u>Product:</u>

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

### SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

### Product:

Toxicity to fish

No data available

### 12.2 Persistence and degradability

### Product:

Biodegradability

No data available

### 12.3 Bioaccumulative potential <u>Product:</u>

## according to Regulation (EC) No. 1907/2006

### SAFETY DATA SHEET

# SÜDWEST SolSilikat Fassadenfarbe

Bioaccumulation	No data available
12.4 Mobility in soil	
Product:	
Mobility	No data available
12.5 Results of PBT and vPv	B assessment
Product:	
Assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
12.6 Other adverse effects	
Product:	
Additional ecological information	The product is alkaline. Do not allow product to enter into ground water, bodies of water or sewage systems.

### SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. Dispose of as special waste in compliance with local and national regulations. Partial and residual quantities can be reused.
Contaminated packaging	Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.
Waste key for the unused product	08 01 12 Waste paint and varnish other than those covered by 08 01 11

### SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

# SÜDWEST SolSilikat Fassadenfarbe

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks

This information is not available.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks

Not applicable

### SECTION 15: REGULATORY INFORMATION

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC	
Directive 2010/75/EU	0,3 % 4,0 g/l
VOC	
Directive 2004/42/EC	0,3 % 4,0 g/l
	EU limit value for this product (cat. A/c) :40 g/IThis product contains max40 g/IVOC.
Regulation (EC) No 649/2012 of the European	Not applicable

649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

# SÜDWEST SolSilikat Fassadenfarbe

Other regulations

Comply with the statutory regulations on health and safety at work.

### 15.2 Chemical safety assessment

This information is not available.

### **SECTION 16: OTHER INFORMATION**

Changes from the previous version are indicated by markings in the left-hand margin.

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP -Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. -Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic

# SÜDWEST SolSilikat Fassadenfarbe

Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS -Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS REG\_EU / EN sdb@suedwest.de

# SÜDWEST SolSilikat Fassadenfarbe